



# BUNKER Pro-6

Self-Powered Sub Bass

- Integrated DSP and remote control
- 6000w Speakers program power
- 6000w class D power amplifier
- dsp controlled

## SB218

## POWER AMP.

GENERAL SPECIFICATIONS		GENERAL SPECIFICATIONS	
Charge Type	6 <sup>th</sup> order sub-woofer	OUTPUT POWER	6X 1000W 3x 2000W
POWER AES standard	3000W	INPUT SENSITIVITY	0.775v
PEAK POWER	6000W	THD	0.02 % A 8 Ohm
COMPONENTS	2 CUSTOM 18"	SLEW RATE	35V/us
FREQUENCY RESPONCE	25Hz-110Hz	VOLTAGE GAIN	54X
SENSITIVITY	106 db	INPUT IMPEDANCE SYM/ASYM	20K/10K
MAXIMUM SPL	143 db continuous, 146 db Peak	DAMPING FACTOR	300
NOMINAL IMPEDANCE	2x 8 Ohm	HUM AND NOISE	>-103db
DISPERSION	OMNI	CONNECTORES	2x XLR F AND (2+) AND 2xSPEAKON 4
IDEAL Crossover Pointes	HPF 23Hz LPF 90 Hz	INTERNAL CROSSOVER	DSP controlled Time correction process
CONSTRUCTION	Heavily braced multi-laminated 18mm plywood finished with black texture paint	LIMITER	0-dbu
CONNECTORES	IN SIDE	COOLING	VARIABLE SPEED FAN
NET WEIGHT	90Kg	PROTECTION	HIGH TEMPI SHORT CIRC/ DC/AUDIO LIMITER/ TURN-ON DELAY/INRUSH CURRENT LIMITER
		POWER SUPPLY	4000 VA



Flood.Lda. - Rua S. Bento nº 186, Casais 3045-119 Coimbra - PORTUGAL

Tel: (00351) 239 048 656 (00351) 917343706 info@flood.pt www.flood.pt